


MMBTSD1781

NPN Silicon Epitaxial Planar Transistor

Medium Power Transistor

The transistor is subdivided into two group Q and R according to its DC current gain.



1. Base 2. Emitter 3. Collector
TO-236 Plastic Package


Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Collector Base Voltage	V_{CBO}	40	V
Collector Emitter Voltage	V_{CEO}	32	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current	I_C	0.8	A (DC)
	I_{CP}	1.5	A (Pulse) ¹⁾
Power Dissipation	P_{tot}	200	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	- 55 to + 150	$^\circ\text{C}$

¹⁾ Single pulse $P_w = 100 \text{ ms}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 3 \text{ V}$, $I_C = 100 \text{ mA}$	h_{FE}	120	-	270	-
	h_{FE}	180	-	390	-
Collector Emitter Breakdown Voltage at $I_C = 1 \text{ mA}$	$V_{(BR)CEO}$	32	-	-	V
Collector Base Breakdown Voltage at $I_C = 50 \mu\text{A}$	$V_{(BR)CBO}$	40	-	-	V
Emitter Base Breakdown Voltage at $I_E = 50 \mu\text{A}$	$V_{(BR)EBO}$	5	-	-	V
Collector Cutoff Current at $V_{CB} = 20 \text{ V}$	I_{CBO}	-	-	0.5	μA
Emitter Cutoff Current at $V_{EB} = 4 \text{ V}$	I_{EBO}	-	-	0.5	μA
Collector Emitter Saturation Voltage at $I_C = 500 \text{ mA}$, $I_B = 50 \text{ mA}$	$V_{CE(sat)}$	-	-	0.4	V
Transition Frequency at $V_{CE} = 5 \text{ V}$, $-I_E = 50 \text{ mA}$, $f = 100 \text{ MHz}$	f_T	-	150	-	MHz
Output Capacitance at $V_{CB} = 10 \text{ V}$, $I_E = 0 \text{ A}$, $f = 1 \text{ MHz}$	C_{ob}	-	15	-	pF



SEMTECH ELECTRONICS LTD.



ISO/TS 16949 : 2009

ISO 14001 : 2004

ISO 9001 : 2008

BS-OHSAS 18001 : 2007

IECQ QC 080000

Certificate No. 160719009

Certificate No. 7116

Certificate No. 507191410

Certificate No. 7116

Certificate No. PRC-HSPM-14831

Dated : 16/03/2015 Rev:01

●Electrical characteristic curves




Fig.1 Grounded emitter propagation characteristics




Fig.2 Grounded emitter output characteristics




Fig.3 DC current gain vs. collector current




Fig.4 Collector-emitter saturation voltage vs. collector current (I)




Fig.5 Collector-emitter saturation voltage vs. collector current (II)




Fig.6 Gain bandwidth product vs. emitter current




Fig.7 Collector output capacitance vs. collector-base voltage





Fig.8 Emitter input capacitance vs. emitter-base voltage



SEMTECH ELECTRONICS LTD.



ISO TS 16949 : 2009

ISO 14001 : 2004

ISO 9001 : 2008

BS-OHSAS 18001 : 2007

IECQ QC 080000

Certificate No. 16071909

Certificate No. 50719416

Certificate No. 7116

Certificate No. PRC-HSPM-148-1

Dated : 16/03/2015 Rev:01